

High temperature burner for cartridge



Item no. 1424

- piezo electric ignition
- needle valve
- T=1600° C

Variants

Article no.

1424

Technical data

Item no.	Max. Temp. (°C)		Consumption (l/h)			Height (mm)		Weight (g)
1424	1550		0.15			50		200

Item no.	Pipe ø	Head Ø	Bel. (kg)	DIN	GS	Natural gas	Propane	Safety base
1424		20	1,50	-	-	-	-	-

Art Gallery

0	4538, 4538, 1424a, 1424a.jpg, 1121311, https://www.usbeck.eu/wp-content/uploads/1424a.jpg , https://www.usbeck.eu/en/products/hochtemperaturbrenner-fuer-kartusche/1424a-2/ , 4, 1424a-2, inherit, 2057, 2025-10-22 09:25:54, 2025-10-22 09:25:54, 0, image/jpeg, image, jpeg, https://www.usbeck.eu/wp-includes/images/media/default.png , 2099, 2126
1	4542, 4542, 1424_klein, 1424_klein.jpg, 2064428, https://www.usbeck.eu/wp-content/uploads/1424_klein.jpg , https://www.usbeck.eu/en/products/hochtemperaturbrenner-fuer-kartusche/1424_klein-2/ , 4, 1424_klein-2, inherit, 2057, 2025-10-22 09:29:36, 2025-10-22 09:29:51, 0, image/jpeg, image, jpeg, https://www.usbeck.eu/wp-includes/images/media/default.png , 4951, 5312